Sealant Tape



FİBERMAK MÜHENDİSLİK MAKİNA KALIP KOMPOZİT SAN.TİC.LTD.ŞTİ 1422 Sokak No:9 Doğanlar Bornova/İZMİR www.fibermakcomposites.com info@fibermakcomposites.com Tel: +90 232 479 65 75 Fax:+90 232 479 65 75

- Economic, low cost vacuum bag sealant tape suitable for ambient, de-bulk and medium temperature applications.
- · Widely used in the wind, marine and glass industries.
- · Excellent tack.
- Also suitable for high temperature envelope bagging applications.
- Material compatible with most substrates (including composite tools) and film materials.
- For optimum results, tape must be allowed to cool to an ambient temperature before stripping from mould surfaces.

PHYSICAL PROPERTIES

Maximum use temperature

Up to 150°C bag to tool

Colour

Black Grey Yellow

AVAILABILITY & PACKAGING

Roll size

15m x 12mm x 3mm (also available as a 4mm diameter bead) 22 rolls

Standard box contents

STORAGE & HANDLING

- Must be stored in it's original containers, under optimum conditions of between 5 and 25°C.
- Material has a two year shelf life from date of manufacture.
- Must be stored flat.
- Boxes should not be stacked more than 5 high.
- Handling of these products must conform to individual company guidelines and health and safety regulations.



Teknoloji hiç bu kadar **hafif** olmamıştı.